

Löschwasserrückhaltung
Gefahrstoffrückhaltung
Hochwasserschutz



THOMAS SYS TECH GmbH • An der Heier 15-17 • 37318 Wahlhausen

Telefon: +49 (0) 3 60 87 / 97 11 0

Fax: +49 (0) 3 60 87 / 97 11 50

Mobil: +49 (0) 1 72 / 6 89 32 01

E-Mail: info@thomas.biz

Internet: www.thomas.biz

Fire water retention barrier
T MB BVD
2 Sided Vertically Pivoting
Manual Barrier

Clear width mm
Barrier height mm

The firewater barrier, certified by TÜV and produced according to VdS guidelines, consists of horizontal left side and right side floor plates each with a hinges mounted to either side of the door. A metal barrier is attached to each swivel point. The barriers are easily rotated upwards or downwards and are locked into place by means of a quick clamp at the center of the door. Opening and closing as well as locking and unlocking occur manually.

Standard fitting:

- quick clamp locking
- Color: RAL 3000 Flame Red

Possible additional options:

- closure control switch
- bumper buffer devices
- gas strut
- spring rope pulley
- chemical resistant PTFE seal
- chemical resistant PPA seal
- galvanized finish
- RAL specialty colors



Bank: Kreissparkasse Eichsfeld
SWIFT/BIC: HELADEF1EIC
IBAN: DE23 8205 7070 0106 0045 90
Steuernummer: 157/121/08387

Es gelten umseitige Allgemeinen Geschäftsbedingungen • AG Jena HRB 505146 • GF Werner Thomas • Umsatzst.-ID.: DE 271 399 240