

**Löschwasserrückhaltung**  
**Gefahrstoffrückhaltung**  
**Hochwasserschutz**



**THOMAS SYS TECH GmbH** • An der Heier 15-17 • 37318 Wahlhausen

Telefon: +49 (0) 3 60 87 / 97 11 0

Fax: +49 (0) 3 60 87 / 97 11 50

Mobil: +49 (0) 1 72 / 6 89 32 01

E-Mail: [info@thomas.biz](mailto:info@thomas.biz)

Internet: [www.thomas.biz](http://www.thomas.biz)

Fire water retention barrier  
**T MB HD**  
Horizontally Pivoting  
Manual Barrier

Clear width ..... mm  
Barrier height ..... mm

The firewater barrier, certified by TÜV and produced according to VdS guidelines, consists of a hinged barrier body on one side and a U-profile receiver on the opposite side. When not in use, the barrier is held in position by a locking mechanism. The barrier is raised manually from its resting position by 90 degrees to the closed position. Upon reaching the closed position, the barrier is lowered and locked into place by means of a quick clamp. Unlocking of the clamps, lifting and resetting and locking of the barrier into its resting position also occur manually.

**Standard fitting:**

- quick clamp locking
- Color: RAL 3000 Flame Red

**Possible additional options:**

- closure control switch
- bumper buffer devices
- chemical resistant PTFE seal
- chemical resistant PPA seal
- galvanized finish
- RAL specialty colors



Bank: Kreissparkasse Eichsfeld  
SWIFT/BIC: HELADEF1EIC  
IBAN: DE23 8205 7070 0106 0045 90  
Steuernummer: 157/121/08387

Es gelten umseitige Allgemeinen Geschäftsbedingungen • AG Jena HRB 505146 • GF Werner Thomas • Umsatzst.-ID.: DE 271 399 240