

**Löschwasserrückhaltung  
Gefahrstoffrückhaltung  
Hochwasserschutz**



**THOMAS SYS TECH GmbH** • An der Heier 15-17 • 37318 Wahlhausen

Telefon: +49 (0) 3 60 87 / 97 11 0  
Fax: +49 (0) 3 60 87 / 97 11 50  
Mobil: +49 (0) 1 72 / 6 89 32 01  
E-Mail: [info@thomas.biz](mailto:info@thomas.biz)  
Internet: [www.thomas.biz](http://www.thomas.biz)

Fire water retention barrier  
**T MB LRA**  
Loading Dock Containment  
Manual Barrier

Clear width ..... mm  
Barrier height ..... mm

The firewater barrier, certified by TÜV and produced according to VdS guidelines, consists of a left side and right side hollowed steel profile. Each hollowed steel profile contains a swivel joint. The swivels attach a U shaped metal barrier body. When not in use, the U shaped barrier body is positioned vertically over the swivels. When needed, the U shaped barrier is lowered to the floor manually per hand crank. Two quick clamps which press the barrier to the floor and prevent unwanted lifting are mounted on the U shaper barrier.

**Standard fitting:**

- hand crank
- quick clamp locking
- Color: RAL 3000 Flame Red

**Possible additional options:**

- closure control switch
- bumper buffer devices
- gas strut
- spring rope pulley
- chemical resistant PTFE seal
- chemical resistant PPA seal
- galvanized finish
- RAL specialty colors



Bank: Kreissparkasse Eichsfeld  
SWIFT/BIC: HELADEF1EIC  
IBAN: DE23 8205 7070 0106 0045 90  
Steuernummer: 157/121/08387

Es gelten umseitige Allgemeinen Geschäftsbedingungen • AG Jena HRB 505146 • GF Werner Thomas • Umsatzst.-ID.: DE 271 399 240