## Löschwasserrückhaltung Gefahrstoffrückhaltung Hochwasserschutz



THOMAS SYS TECH GmbH • An der Heier 15-17 • 37318 Wahlhausen

Fire water retention barrier T MB PG Permanently Bolted Manual Barrier

Clear width ..... mm Barrier height ..... mm

The TÜV and VdS certified firewater barrier consist of an L-shaped steel profile bolted to the floor and sealed water tight. The length of the barrier can be extended infinitely by means of various connective possibilities.

## **Standard fitting:**

- Color: RAL 3000 Flame Red

## **Possible additional options:**

- bumper buffer devices
- chemical resistant PTFE seal
- chemical resistant PPA seal
- galvanized finish
- RAL specialty colors



Bank: Kreissparkasse Eichsfeld SWIFT/BIC: HELADEF1EIC IBAN: DE23 8205 7070 0106 0045 90 Steuernummer: 157/121/08387

			I
F	elefon: ax: 1obil: -Mail:	+49 (0) 3 60 87 / 97 11 +49 (0) 3 60 87 / 97 11 +49 (0) 1 72 / 6 89 32 in f o @ t h o m a s . b	50 01

Internet:

www.thomas.biz

Es gelten umseitige Allgemeinen Geschäftsbedingungen • AG Jena HRB 505146 • GF Werner Thomas • Umsatzst.-ID.: DE 271 399 240