

Löschwasserrückhaltung
Gefahrstoffrückhaltung
Hochwasserschutz



THOMAS SYS TECH GmbH • An der Heier 15-17 • 37318 Wahlhausen

Telefon: +49 (0) 3 60 87 / 97 11 0

Fax: +49 (0) 3 60 87 / 97 11 50

Mobil: +49 (0) 1 72 / 6 89 32 01

E-Mail: info@thomas.biz

Internet: www.thomas.biz

Fire water retention barrier

T M B S

Insertable

Mobile Barrier

Clear width mm

Barrier height mm

The TÜV and VdS certified firewater barrier consists of one left side U-profile and one right side U-profile which can either be mounted in or in front of the opening as well as a metallic barrier made of thermally and mechanically resistant hollow-chamber profile. The barrier is set into the U-profile and locked into place. Unlocking and removal occur manually. 2 L-shaped wall mounts are provided for storage outside of the U-profile.

Standard fitting:

- wall mount
- quick clamp locking
- Color: RAL 3000 Flame Red

Possible additional options:

- closure control switch
- bumper buffer devices
- protective cover
- medium clamp (> 4000 mm)
- (mobile) H-profile
- stainless steel model
- galvanized finish
- barrier stand
- forklift eyelets
- chemical resistant PTFE seal
- chemical resistant PPA seal
- RAL specialty colors



Bank: Kreissparkasse Eichsfeld

SWIFT/BIC: HELADEF1EIC

IBAN: DE23 8205 7070 0106 0045 90

Steuernummer: 157/121/08387

Es gelten umseitige Allgemeinen Geschäftsbedingungen • AG Jena HRB 505146 • GF Werner Thomas • Umsatzst.-ID.: DE 271 399 240