Löschwasserrückhaltung Gefahrstoffrückhaltung Hochwasserschutz



THOMAS SYS TECH GmbH • An der Heier 15-17 • 37318 Wahlhausen

+49 (0) 3 60 87 / 97 11 0 Telefon: Fax: +49 (0) 3 60 87 / 97 11 50 +49 (0) 1 72 / 6 89 32 01 Mobil: E-Mail: info@thomas.biz Internet: www.thomas.biz

Clear width mm Barrier height mm

The barrier, certified by TÜV and produced according to VdS guidelines, consists of one left side U-profile and one right side U-profile which can be mounted in or in front of the opening as well as a hollow-chamber, thermally and mechanically resistant metal barrier. The two metal barriers are set into the U-profile and locked into place using two quick clamps. Unlocking and removal also occur manually. Two L-shaped mounts are provided for storage of the barriers when they are not in place in the U-profile.

Standard fitting:

- wall mount

Flood barrier

Stackable Insertable Mobile Barrier

T MB SS

- galvanized finish
- quick clamp locking
- Color: RAL 3000 Flame Red

Possible additional options:

- bumper buffer devices
- protective cover
- medium clamp (> 4000 mm)
- (mobile) H-profile
- barrier stand
- forklift eyelets
- RAL specialty colors

















Bank: Kreissparkasse Eichsfeld SWIFT/BIC: HELADEF1EIC IBAN: DE23 8205 7070 0106 0045 90 Steuernummer: 157/121/08387

Es gelten umseitige Allgemeinen Geschäftsbedingungen • AG Jena HRB 505146 • GF Werner Thomas • Umsatzst.-ID.: DE 271 399 240