

**Löschwasserrückhaltung**  
**Gefahrstoffrückhaltung**  
**Hochwasserschutz**



**THOMAS SYS TECH GmbH** • An der Heier 15-17 • 37318 Wahlhausen

Telefon: +49 (0) 3 60 87 / 97 11 0  
Fax: +49 (0) 3 60 87 / 97 11 50  
Mobil: +49 (0) 1 72 / 6 89 32 01  
E-Mail: [info@thomas.biz](mailto:info@thomas.biz)  
Internet: [www.thomas.biz](http://www.thomas.biz)

Fire water retention barrier  
**T MB SS**  
Stackable Insertable  
Mobile Barrier

Clear width ..... mm  
Barrier height ..... mm

The firewater barrier, certified by TÜV and produced according to VdS guidelines, consists of one left side U-profile and one right side U-profile which can be mounted in or in front of the opening as well as a hollow-chamber, thermally and mechanically resistant metal barrier. The two metal barriers are set into the U-profile and locked into place using two quick clamps. Unlocking and removal also occur manually. Two L-shaped mounts are provided for storage of the barriers when they are not in place in the U-profile.

**Standard fitting:**

- wall mount
- quick clamp locking
- Color: RAL 3000 Flame Red

**Possible additional options:**

- closure control switch
- bumper buffer devices
- protective cover
- medium clamp (> 4000 mm)
- (mobile) H-profile
- stainless steel model
- galvanized finish
- barrier stand
- forklift eyelets
- chemical resistant PTFE seal
- chemical resistant PPA seal
- RAL specialty colors



Bank: Kreissparkasse Eichsfeld  
SWIFT/BIC: HELADEF1EIC  
IBAN: DE23 8205 7070 0106 0045 90  
Steuernummer: 157/121/08387

Es gelten umseitige Allgemeinen Geschäftsbedingungen • AG Jena HRB 505146 • GF Werner Thomas • Umsatzst.-ID.: DE 271 399 240